



# FLOORING

## INSTALLATION GUIDELINES

**SOLIDWOOD®**  
Natural - Durable - Sustainable



We  to  
Talk wood!

THANK YOU FOR YOUR  
PURCHASE!

**SOLIDWOOD®**  
Natural - Durable - Sustainable

Congratulations with your new Solid Wood Flooring!  
We have prepared this presentation for your Flooring  
installation guide.

We are available for any further questions that you  
may have, and we thank you for your purchase.





01

# PREPARATION OF FLOORING

Installation team ensures the safe and high-quality installation of your solid wood flooring.



# Pest Control

- Most solid hardwoods are quite resistant, but the best way to avoid termites is to treat the perimeter of your residence. Contact your trusted pest control company for the best result.

**SOLIDWOOD®**  
Natural - Durable - Sustainable



# Preparation of Subfloor

- Please ensure that there is min. 2" concrete topping.
- Please remember to mark all the utilities that should be embedded in the flooring.
- Ensure that the sub-floor is level and with a smooth finish. It must be completely dry to prevent any deformation.
- The Concrete slab must be level with no more than 3mm deviation over a 3 meter radius.





# Area must be dry

- The rooms in which the flooring will be installed must be fully covered to prevent water from entering the room. Roof and windows must be finished before the flooring.
- Wood flooring should be one of the last jobs aside from final paint of the structure completed on the construction project.
- Limit foot traffic on the finished floor, and we recommend protecting it against any paint and step marks.





02

FOR FLOORING  
INSTALLATION GUIDE

Filtratimber ensure to make your flooring well-built and durable during the installation.



# Installation of subfloor

- Over a levelled slab lay a minimum of 1/2" Marine plywood. Attach the sheets to the slabs using screw or nails. Level the plywood as necessary by plane and secure the area.



**SOLIDWOOD®**  
Natural - Durable - Sustainable



# Installation of wood planks

- After installing subfloor, it is now time to layout in desired pattern and install our wood planks with the use of tucker nails and adhesive.



**SOLIDWOOD®**  
Natural - Durable - Sustainable



# Sanding of the Floors

- With the wood planks now securely in place, the next step is to sand the floors to achieve a smooth and even surface.



**SOLIDWOOD®**  
Natural - Durable - Sustainable



# Application of Sealer

- Prior to applying the topcoat, a sealer/primer is applied to ensure a smooth and even surface, effectively preparing the floor for the final finish and slight sanding if needed.
- With the preparation complete, the final touch is now added to the flooring with a topcoat of your choice.



**SOLIDWOOD**<sup>®</sup>  
Natural - Durable - Sustainable



# SOLIDWOOD®

Natural - Durable - Sustainable



SOLIDWOOD brand is fully owned by FILTRA Timber, the Philippines' leading importer/distributor of sustainable timber products.

[www.filtratimber.com](http://www.filtratimber.com)